

# 19" Floor Standing Cabinet

for structured cabling and telecommunications



## The line of cabinets that fully meets the needs of installers

The **Intellinet** cabinets are the result of an innovative project that meets the needs of structured cabling in data and telecommunications networks.

-  **Versatility:** pair of 19" front and rear adjustable rails equipped with scales, cables inlet from top or bottom side; 100 mm blind plinth with removable panels; opening on the bottom to facilitate the air flow.
-  **Robustness:** guarantees static capacity up to 500 Kg (220 Kg on wheels) thanks to the 2 mm steel uprights structure and 3 mm of the innovative corner joint.
-  **Quick assembly:** blind and removable side and rear panels with a 1/4 turn lock; door in tempered glass complies to UNI EN121 50-1 norm is reversible with lock and quick release hinges.
-  **IP20 protection degree** according to EN 60529 standard.
-  **Accessories:** wide range of accessories to meet the needs of designers and installers.



MAXIMUM VERSATILITY



BICOLOR LOOK



RAILS WITH SCALE

italiana QUALITÀ

**MADE IN ITALY** CE certified product according to EN 62208 and manufactured according to the following international standards: IEC 297-1 / 2/3; EN 61439-1; EN 60529; EN 12150-1 and in compliance with the ISO 9001: 2008 standard



# 19" Floor Standing Cabinet

for structured cabling and telecommunications



600 and 800 mm in depth and width



### Technical features:

- Sturdy cabinet with 2 mm uprights and innovative 3 mm corner joints
- Panels and front door easily removable to facilitate the installation of the equipment
- Reversible front door with quick-release hinges and handle with key lock
- Sides removable blind panels with ¼ turn system
- Blind or 85% vented sheet metal back panels
- Top ready with holes for ventilation system and provided with cable entry
- Bottom ready for cable entry and equipped with a small door that closed allows you to place equipment as UPS, open allows ventilation
- Supplied with a pair of 19" front and rear rails with scale
- Complete with blind plinth (h 100 mm) or feet
- Static load capacity 500 kg, 220 kg on wheels
- Protection degree IP20
- Includes grounding kit
- Color RAL7035 (grey) or RAL9005 (black)

Cardboard packaging with transparent film for immediate ascertainment of the product's integrity



### Accessories:

for perfect cabling solutions, the Network Rack can be configured with all Intellinet accessories.

Available double glass or vented swing door



CODE	U	SIZE			USABLE		color	front panel	back panel	bottom
		W mm	D mm	H mm	W mm	D mm				
I-CASE EP-2060GT	20	600	600	1079	486	575	grey	glass	blind	feet
I-CASE EP-2060BKT	20	600	600	1079	486	575	black	glass	blind	feet
I-CASE EP-2760GT	27	600	600	1390	486	575	grey	glass	blind	plinth
I-CASE EP-2760BKT	27	600	600	1390	486	575	black	glass	blind	plinth
I-CASE EP-3360GT	33	600	600	1656	486	575	grey	glass	blind	plinth
I-CASE EP-3360BKT	33	600	600	1656	486	575	black	glass	blind	plinth
I-CASE EP-4260GT	42	600	600	2057	486	575	grey	glass	blind	plinth
I-CASE EP-4260BKT	42	600	600	2057	486	575	black	glass	blind	plinth
I-CASE EP-2780GT	27	600	800	1390	486	775	grey	glass	blind	plinth
I-CASE EP-2780BKT	27	600	800	1390	486	775	black	glass	blind	plinth
I-CASE EP-3380BKT	33	600	800	1656	486	775	black	glass	blind	plinth
I-CASE EP-3880GT	38	600	800	1879	486	775	grey	vetro	blind	plinth
I-CASE EP-3880BKT	38	600	800	1879	486	775	black	glass	blind	plinth
I-CASE EP-4280GT	42	600	800	2057	486	775	grey	glass	blind	plinth
I-CASE EP-4280BKT	42	600	800	2057	486	775	black	glass	blind	plinth
I-CASE EPX-428GTX	42	800	800	2057	686	775	grey	glass	blind	feet
I-CASE EPX-428BKX	42	800	800	2057	686	775	black	glass	blind	feet
I-CASE EPX-428BKV	42	800	800	2057	686	775	black	80% vented single door	80% vented	feet
I-CASE EPX-428BK2	42	800	800	2057	686	775	black	75% vented double door	80% vented	feet
I-CASE EPX-478BKX	47	800	800	2279	686	775	black	glass	blind	feet

