



Power Delivery Wall Charger - 27 W

USB-C Power Delivery Port up to 18 W, USB-A Charging Port up to 12 W / 2.4 A,
Black

Part No.: **102148**

Power up your devices with a portable, powerful Power-Delivery charger.

Enjoy plenty of charging power with the Manhattan Power Delivery Wall Charger - 27 W. This wall charger uses Power Delivery (PD) technology to power up any device with a USB-C charging port, from a laptop to a mobile phone or a handheld game console, and the additional USB-A port can fast charge any handheld device or tablet. The perfect power companion for travelers with its stylish, compact and ultra-modern design, the Manhattan Power Delivery Wall Charger - 27 W also intelligently safeguards itself and your devices with short-circuit-, overvoltage-, overcurrent- and overtemperature-protection functions.

Features:

- Two-device charging solution with USB-C Power Delivery (PD 3.0) and USB-A charging ports
- Charges two different devices simultaneously with ideal potential energy
- USB-C PD port delivering up to 18 W to charge a handheld game console, tablet or other compatible device
- USB-A port delivering up to 5 V / 2.4 A to fast charge a compatible portable device
- Total power output of 27 W shared between the two ports*
- Overload, overcurrent and overheat protection
- Compact, portable and stylish design for easy travel

For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com.

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

- Three-year warranty
- * When simultaneously charging, USB-C port delivers 5 V / 3 A and USB-A port delivers 5 V / 2.4 A

Specifications:

Standards and Certifications

- USB 2.0
- PD 3.0
- CE
- RoHS
- WEEE

Ports

- One USB-C with Power Delivery (PD 3.0)
- One USB-A

General

- AC input: 100 – 240 V; 50 – 60 Hz
- USB-C output: 5 – 12 V; maximum 3 A; 18 W
- Voltage/current settings (maximum):
 - USB-C:
 - 5 V / 3 A
 - 9 V / 2 A
 - 12 V / 1.5 A
 - USB-A:
 - 5 V / 2.4 A

Input Characteristics

- AC rated voltage: 100 – 240 V
- Frequency range: 50 – 60 Hz (± 1 Hz)
- Current: ? 1 A at 100 VAC 60 HZ

Output Characteristics

- Rated voltage: 5 / 9 / 12 V
- Current: 3 A maximum (at constant voltage mode)
- Rated power: 27 watts maximum
- Overshoot voltage: ? 5%

Protection Characteristics

- Short circuit (SCP) with auto-recovery mode
- Overvoltage (OVP) with auto-recovery mode
- Overcurrent (OCP) — current limit: 150% (max)
- Overtemperature (OTP)

Physical

- Dimensions: 9.5 x 4.4 x 2.6 cm (3.74 x 1.73 x 1.02 in)

- Weight: 0.07 kg (1.41 oz.)
- Housing: plastic

Operating Environment

- Operation Temperature: 0 – 30°C (32 – 86°F)
- Storage Temperature: -20 – 65°C (-4 – 149°F)
- Humidity (noncondensing): 10 – 90%

Package Contents

- Power Delivery Wall Charger - 27 W
- Quick Instruction Guide

