

Power Delivery Wall Charger - 18 W

USB-C Power Delivery Port up to 18 W, Europlug, Black
Part No.: 102087

A portable, powerful Power-Delivery-capable charger

Enjoy ample charging power with the Manhattan Power Delivery Wall Charger - 18 W. This wall charger uses Power Delivery (PD) technology to power up any device with a USB-C charging port, from a handheld game console to a mobile phone. The perfect companion for travelers with its stylish, compact and ultra-modern design, the Manhattan Power Delivery Wall Charger - 18 W also intelligently safeguards itself and your devices with short-circuit-, overvoltage-, overcurrent- and overtemperature-protection functions.

Features:

- USB-C PD 3.0 port delivering up to 18 W to charge a handheld game console, tablet or other compatible device
- Overload, overcurrent and overheat protection
- Compact, portable and stylish design for easy travel
- Three-year warranty

Specifications:

Standards and Certifications
• USB 2.0
• PD 3.0
• CE
• RoHS
• WEEE

For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com.
All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

Ports
• One USB-C with Power Delivery (PD 3.0)

General
• AC input: 100 – 240 V; 50 – 60 Hz
• USB-C output: 5 – 12 V; maximum 3 A; 18 W
• Voltage/current settings (maximum):
- USB-C:
- 5 V / 3 A
- 9 V / 2 A
- 12 V / 1.5 A

Input Characteristics
• AC rated voltage: 100 – 240 V
• Frequency range: 50 – 60 Hz (±1 Hz)
• Current: ? 1 A at 100 VAC 60 HZ

Output Characteristics
• Rated voltage: 5 / 9 / 12 V
• Current: 3 A maximum (at constant voltage mode)
• Rated power: 18 watts maximum
• Overshoot voltage: ? 5%

Protection Characteristics
• Short circuit (SCP) with auto-recovery mode
• Overvoltage (OVP) with auto-recovery mode
• Overcurrent (OCP) — current limit: 150% (max)
• Overtemperature (OTP)

Physical
• Dimensions: 6 x 3.9 x 2.2 cm (2.58 x 2.58 x 1.5 in)
• Weight: 0.04 kg (1.41 oz.)
• Housing: plastic


Operating Environment
• Operation Temperature: 0 – 30°C (32 – 86°F)
• Storage Temperature: -20 – 65°C (-4 – 149°F)
• Humidity (noncondensing): 10 – 90%

Package Contents
• Power Delivery Wall Charger - 18 W
• Quick Instruction Guide

For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com.
All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.









For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com.
All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.