

LogiLink®



Indoor Air Quality Monitor CO₂ Alarm

Art. No.: SC0117

Monitor Your Air Quality Anytime, Anywhere

Indoor Air Quality Monitor CO₂ Alarm is your best air quality detection solution. Easy to use real-time monitoring and tracking of air quality, temperature and humidity in the environment you are in. With the easy-to-read display, it intuitively simplifies data readings. The compact size with built-in lithium battery is especially designed for travel. Perfect for home, schools, offices, camping areas and anywhere high levels of carbon dioxide are generated.



CO₂



Humidity



Temperature



Alarm



3 State Indication



Touch Screen



Mute



*The specifications and pictures are subject to change without prior notice.
*All trade names referenced are the registered trademarks of their respective owners.



SC0117



4 052792 066920

Made in China

Easy to Read, Easy to Control

Large LCD to monitor CO₂ concentration (5000 ppm range), temperature and humidity simultaneously. Avoid home or health problems as it tips you off to potential sources of CO₂.



Good
(400–799 ppm)



Caution
(800–1599 ppm)



Bad
(1600–5000 ppm)

Always Stay Informed

Receive audible and visual alarms when concentration levels go above 1600 ppm. The visual alarm LED indicator displays real-time air quality levels (green=good, yellow=caution, red=bad).

All Day Long

With a built-in 2000 mAh battery, it supports a working time of up to 16 hours and can be charged via micro USB easily.



Micro USB Charging Port



Designed for On-the-Go

Comes with a magnetic wall mount and stand; conveniently attach it on the wall, or put it on the desk or the floor. The compact and lightweight makes it great to travel with.



Designed for any high concentration area such as schools, offices, shops, or camping areas to measure air quality anytime.



*The specifications and pictures are subject to change without prior notice.
 *All trade names referenced are the registered trademarks of their respective owners.



Made in China

Specifications:

Sensor (chips)	NDIR
Power By	USB DC 5 V/1 A
Standby Current	4 mA
Working Current	Average 140 mA, max. 425 mA
Working Time	Up to 16 hours
LCD Display Status	Power, Temperature, Humidity, CO ₂ , Alarm, On/Off
Alarm Sound Sentivity	3 sounds/max. 85 dB
Alarm Switch Button	Touch On/Off on the display
Low Power Indication	Yes
Temperature Detect Range	0–65°C
Humidity Detect Range	0–100% RH (no condensation)
CO ₂ Detect Range	400–5000 ppm
Temperature Torlerance	±1°C
Humidity Torlerance	±5% RH (no condensation)
CO ₂ Measuring Tolerance	±50 ppm and ±5%
Battery	3.7 V Lithium battery
Battery Capacity	2000 mAh
Display Brightness	3 levels: Low, Medium, High
LED Indicator	Indicator for CO ₂ Concentration(ppm) Green LED for 400–799 ppm Yellow LED for 800–1599 ppm Red LED for 1600–5000 ppm
Alarm Trigger	Activity when CO ₂ up to 1600 ppm
Reset	AUTO when swtich on
Standby Power Consumption	14,8 mW
Power Consumption (max.)	1,5725 W
Housing Material	ABS
Operating Temperature	0–50°C
Operating Humidity	0–90% RH (no condensation)
Storage Temperature	-20–70°C
Storage Humidity	0–90% RH (no condensation)
Dimensions	10x10x3 cm
Weight	128 g

Package Contents:

- » 1x Indoor Air Quality Monitor
- » 1x USB Charging Cable
- » 1x User Manual

Package Information:

- » Packing Dimension: mm
- » Packing Weight: kg
- » Carton Dimension: mm
- » Carton Q'ty: pcs
- » Carton Weight: kg



*The specifications and pictures are subject to change without prior notice.
*All trade names referenced are the registered trademarks of their respective owners.



SC0117



Made in China