



10064

LINKACT

5 Port, Metal Chassis

VINTELLINE*

gabic Ethernet

Gigabit Ethernet Desktop Switch

POWER 1

This switch includes five Gigabit ports, and is easy to install with its auto-learning capabilities.

The INTELLINET NETWORK SOLUTIONS Gigabit Ethernet Desktop Switch is perfect for the home or small office, delivering top speeds to the desktop to satisfy your demanding network needs. The compact design allows it to be installed on the desk, while the rugged metal housing offers protection, as well.

High-Speed Performance

This desktop switch includes five Gigabit Ethernet ports, providing you with high performance on your network to handle quick transfer speeds to support disk mirroring, data backup, graphics image file transfers and other bandwidth-intensive applications.

Auto Features

This network LAN switch includes many auto features that make it easy to use. No configuration is required, making installation Plug and Play and hassle free. And Auto-MDI/MDI-X crossover on all ports eliminates the need for any crossover cables. Each of the five ports on this network LAN switch automatically senses the link speed of the connected network device and adjusts to 10, 100 or 1000 Mbps for compatibility and maximum performance.

Reliable Operation

The Gigabit Ethernet Desktop Switch supports flow control when operating in half duplex mode, and supports IEEE 802.3ab in full duplex mode, ensuring that your data transfer and network connectivity continue to run smoothly and uninterrupted. This, in conjunction with the broadcast storm control and the store and forward switching method, further ensure that your connections remain active even under extremely busy conditions.

Lifetime Warranty

Strict manufacturing standards ensure the highest quality in all INTELLINET NETWORK SOLUTIONS products. All items carry a full Lifetime Warranty — the strongest quality commitment anyone can make.







S INTELLINET

Gigabit Ethernet Desktop Switch

POWER 1

Model 530378

Features

- 5 10/100/1000 auto-sensing Auto MDI-X ports automatically detect optimal network speeds
- Full flow control support provides optimum performance
- Auto-learning of network configuration
- High performance, half and full duplex, with zero packet loss
- Rugged metal housing for maximum durability
- Supports jumbo frames up to 9.6 kBytes
- Supports up to 8,192 MAC address entries
- 112 kBytes buffer memory
- Lifetime Warranty

Specifications

STANDARDS

1000M

LINK/ACT

- IEEE 802.3 (10Base-T Ethernet)
- IEEE 802.3u (100Base-TX Fast Ethernet)
- IEEE 802.3ab (Gigabit Ethernet)
 IEEE 802.3x (Flow Control and
- Backpressure)

GENERAL

- ANSI/IEEE 802.3 NWay auto-negotiation
- Non-blocking, store and forward switching architecture
- Backpressure flow control for half duplex
- mode on 10/100 Mbps ports Connectors: 5 10/100/1000 Mbps RJ-45
- ports
- Switch architecture: store and forward switch technology

- Network cables:
 10Base-T: Cat3, 4, 5 UTP/STP
 100Base-TX: Cat5 UTP/STP
- 1000Base-T: Cat5e UTP/STP
- Certifications: FCC Class B, CE Mark,
- RoHS

PERFORMANCE

- Filter/forward rate
 10BaseT: 14,880 pps (packets per second) - 100Base-TX: 148,800 pps (packets per
- second)
- 1000Base-T: 1,480,000 pps (packets per
- second) • MAC address table: 8,192 entries
- Buffer size: 112 kBytes
- Jumbo frame support: 9.6 kB

LEDS

- Powe • LINK/ACT for each 10/100/1000 Mbps
- 1000 Mbps Link

For more information on INTELLINET NETWORK SOLUTIONS products, consult your local dealer or visit **www.intellinet-network.com**.



Copyright © INTELLINET NETWORK SOLUTIONS

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

POWER • DC input: 7.5 V, 0.8 A

• Power consumption: 10 Watts (maximum)

ENVIRONMENTAL

- Metal housing, desktop size
 Dimensions: 130 (W) x 77 (L) x 25 (H) mm
- (5.1 x 3.0 x 1.0 in.)
- Weight: 0.28 kg (0.6 lbs.)
- Operating temperature: 0 55°C (32
- 131°F)
- Operating humidity: 10 90% RH, non-
- Storage Temperature: -20 90°C (-4 194°F)

PACKAGE CONTENTS

- 5 Port Gigabit Ethernet Desktop Switch
- External power adapter
- User manual