

# HI-SPEED USB 2.0 TO FAST ETHERNET MINI-ADAPTER QUICK INSTALL GUIDE

MODEL 524766

Thank you for purchasing this INTELLINET NETWORK SOLUTIONS™ Hi-Speed USB 2.0 to Fast Ethernet Mini-Adapter, Model 524766.

Easy to install through a handy USB connector, it lets you upgrade your desktop or notebook computer to operate at 10/100 Mbps speeds on the LAN. (See back for Installation instructions and Specifications.)



- 10 times faster than USB 1.1 to Fast Ethernet adapters
- Plug and Play installation and hot-swappable: no need to power down or open up your computer
- Includes USB 2.0 cable
- Full duplex with auto-speed detection
- Low power consumption via a USB bus
- Lifetime Warranty



**INTELLINET**  
NETWORK SOLUTIONS

INTELLINET NETWORK SOLUTIONS™ offers a complete line of active and passive networking products. Ask your local computer dealer for more information or visit

**[www.intellinet-network.com](http://www.intellinet-network.com)**

Copyright © INTELLINET NETWORK SOLUTIONS

All products mentioned are trademarks or registered trademarks of their respective owners.

INT-524766-miniQIG-0509-01

# INSTALLATION

1. Place the included Setup CD in your CD-ROM drive. The InstallShield Wizard will display a Start Installation screen. Click "Next."
2. When the Ready to Install the Program screen displays, click "Install."
3. The Setup Status screen will display, indicating the progress of the procedure with a status bar.
4. When the InstallShield Wizard Complete screen displays, select "Yes, I want to restart my computer now"; then click "Finish."
5. Restart your computer to complete the installation process.

**NOTE:** The sample InstallShield Wizard screen at right has been modified to fit the page.



# SPECIFICATIONS

## STANDARDS

- USB Specification version 2.0
- USB Specification version 1.1
- USB Specification version 1.0
- IEEE 802.3 (10Base-T Ethernet)
- IEEE 802.3u (100Base-TX Fast Ethernet)

## GENERAL

- USB type-A connector
- RJ45 connector
- Certifications: FCC Class B, CE Mark, RoHS, Canada ICES-003 Class B, VCCI Class B, EN 55 022 (CISPR 22) Class B

## ENVIRONMENTAL

- Dimensions: 67 (L) x 20 (W) x 18 (H) mm (2.6 x 0.8 x 0.7 in.)
- Weight: 46 g (1.6 oz.)

- Operating temperature: 0 – 45°C (32 – 113°F)
- Storage temperature: 20 – 70°C (4 – 158°F)
- Operating humidity: 10 – 90%, non-condensing
- Storage humidity: 5 – 95%, non-condensing

## SYSTEM REQUIREMENTS

- Pentium-based system with USB 1.1 or USB 2.0 port
- Windows 2000/XP/Vista

## PACKAGE CONTENTS

- Hi-Speed USB 2.0 to Fast Ethernet Mini-Adapter
- USB 2.0 cable
- Setup CD
- Quick install guide