

Dual Rail VGA LCD KVM Switch, 17" monitor



VGA KVM control platform is one with integrate a single ports KVM switch, monitor, keyboard & mouse into 1U height. It controls 1pcs computer with one platform (keyboard, mouse and monitor).

FEATURES:

Control Platform

- ◆ Control platform with LCD, keyboard, mouse and single ports VGA KVM switch.
- ◆ 1U height, suitable for 19" standard cabinet installation and metal structure.
- ◆ 17" LED screen with high brightness, high clear and high resolution.
- ◆ Control platform can be totally pulled out from the cabinet and the LCD screen can be turned on to 120 degrees.
- ◆ With dual rail structure, the monitor and keyboard can be pulled out respectively.
- ◆ Ultra thin keyboard with keypad.
- ◆ Mouse touch board with two function button.
- ◆ Front panel with lock to prevent damage by accident.
- ◆ Built-in power.
- ◆ Automatic power on/off. When pulling control platform out from cabinet, the power turns off automatically. When pushing it into the cabinet, the power turns on automatically.
- ◆ An easy to use OSD menu.

Switch

- ◆ One control platform can control 1pcs computer by direct connection.
- ◆ Be compatible with USB/PS.2 standard interface.
- ◆ Support VGA, SVGA, XGA video input.
- ◆ Accord with DDC, DDC2, DDC2B standard and VESA standard.
- ◆ Support maximum resolution of 1920 * 1080
- ◆ Support multiple operating systems: WIN95/98/98SE/ME/200/XP/7/ NT, UNIX, LINUX.

SPECIFICATION:

Computer Connection		1
CPU Port Selection		Front panel buttons/OSD menu
Console Connector	Keyboard	Disassembled standard 99-key keyboard
	Mouse	standard PS/2 touch pad; rear side with USB connector
	Video	17 inch SXGA color TFT-LCD
Cable Connectors	Keyboard	1 x PS/2 female (purple), 1 x USB female
	Mouse	1 x PS/2 female (green) , 1 x USB female
	Video	1 x HDB-15 male (blue)
LED's	Online	1 red LED's
	Selected	1 green LED's
LCD monitor	monitor	17.0" SXGA Color TFT-LCD
	visible square	304.128(H)*228.096(V)mm
	Resolution(max)	1920*1080 60HZ
	Support Color	16.2 M / 262K colors
	White Luminance	250 (center, Typ)@ 60 mA
	contrast	700:1 (Typ)
	Back light	LED
	Pixel Pitch	0.297(per one triad)x0.297
	LCD MTBF	50,000hours
	Input power	DC 12 V
Keyboards	keyboard	99keys
	Compatible IBM/AT	Win95/98/98SE/ME/200/Win7 XP Vista WinNT Uni Linux
	Port	Standard PS/2&USB
	Using life	>1,000,000 times
Mouse	X/Y resolution	1000dots/inch 40x40/mm)
	hardware connector	Standard PS/2&USB
	Os support	Win95/98/98SE/ME/200/Win7 XP Vista WinNT Uni Linux
	Using life	>1,000,000 times
Power	Power (AC)	~100V-240V
	Using life	MTBF>60,000hours 25 °C
Housing		Metal (black)
Gross weight		21.35 KGS
Dimensions		640*443*42mm
Installation Dimension		600mm ~ 800mm(adjustable)
Operating/storage Temp		0 ~ 50 /-20 ~ 60 °C